

**Marca: SUNWARD**  
**Modelo: SWE 60UF**

Precio: POA

Ref: SUN5009

**Marca / modelo:** SUNWARD SWE 60UF

**Año:** 2025

**Condición:** Brand New

**Otras especific.:**

- Machine weight: 5750kg
- 5 year warranty
- 3 year full engine warranty
- Kubota EU stage V engine
- Complete with 3 buckets
- Hydraulic quick hitch
- Zero tail swing
- 2 speed tracking













SWE60UF Technical Parameters		
Overall dimension (L x W x H)	mm	5500X1980X2550
A Length to center of rollers	mm	1965
B Total track length	mm	2490
C Ground clearance of platform	mm	640
D Platform tail slewing radius	mm	1050
E Chassis width	mm	1980
F Track width	mm	400
G Chassis clearance from the ground	mm	330
H Track height	mm	575
I Total length	mm	5500
J Cab roof height	mm	2550
K Upper-carriage width	mm	1845
a Max. cutting height	mm	5610
b Max. unloading height	mm	3950
c Max. digging depth	mm	3710
d Max. vertical digging depth	mm	3199
e Max. digging reach	mm	6235
f Max. digging reach at ground level	mm	6105
g Max. lift height of the dozer blade	mm	445
h Max. digging depth of the dozer blade	mm	400
i Swing radius (min.)	mm	2475
Dozer blade length x width	mm	1960X390
Machine weight	kg	5700
with rubber track	kg	5770
with steel track	kg	5770
Standard bucket capacity	m <sup>3</sup>	0.18
Digging force (bucket) (ISO)	kN	46.8
Digging force (arm) (ISO)	kN	31.1
Maximum traction force	kN	49
Slew angle (boom)	°	R50/L70
Traveling speed (Max/Min)	km/h	4.07/2.43
Gradeability	°	35
Ground pressure	kPa	33.87
Swing speed	rpm	9.4
Brand		KUBOTA
Model		V2607-DI-T-ET21
Type		4-cylinder and 4-stroke water cooling
Displacement	L	2.615
Power/speed (gross/net)	kW/rpm	36.5/2000 36/2000
Fuel tank capacity	L	70
Primary pump		2 variable plunger pumps and 1 gear
Displacement	L/min	2x59+42
Pressure of main relief valve	MPa	2x24.5+21
Hydraulic tank capacity	L	70



**Load Capacity:**

R/Ratio	L/R Point Radius(3.0m)		L/R Point Radius(5.0m)		L/R Point Radius(4.0m)		L/R Point Radius(3.0m)	
	Over-Height	Over-Depth	Over-Height	Over-Depth	Over-Height	Over-Depth	Over-Height	Over-Depth
4.0	915.0"	832.0"	—	—	—	—	—	—
3.0	788.0"	675.0"	—	—	1080.0"	837.5"	—	—
2.0	706.0"	577.5"	753.8"	637.8"	1126.0"	930.0"	1890.0"	1402.0"
1.0	575.0"	547.5"	682.5"	607.5"	855.0"	847.5"	1290.0"	1090.0"
0.0	652.5"	540.0"	630.0"	577.5"	807.5"	785.0"	1150.0"	1135.0"
-1.0	682.5"	690.0"	—	—	862.5"	755.0"	1287.8"	1065.0"
-2.0	786.0"	727.5"	—	—	855.0"	750.0"	1140.0"	980.0"

**Notes:**

1. Load with \* is limited by hydraulic capacity and based on ISO 10567. Rated loads do not exceed 87% of hydraulic capacity.
2. Load without \* is limited by tipping load and based on ISO 10567. Rated loads do not exceed 75% of tipping capacity.

Registrada en Inglaterra y Gales Número de empresa: 03184184